


Product Code : F01+HLM-2115
Power : 15W



Powered by:
BRIDGELUX
The Magic of Light™



HOUSING	LED Housing :	Aluminium Die-Casting
	Body Finish :	White Powder Coated
	Reflector :	Metallized PC
	Heat Shrink :	Aluminium Die-Casted Powder Coated

TECHNICAL SPECIFICATION	Light Source :	BRIDGELUX LED
	Beam Angle :	40°
	CCT :	3000K / 4000K / 5000K
	CRI :	80
	Chip Lumens (4K) :	1800 LM (120Lm/w)
	System Lumens (4K) :	1725 LM (115Lm/w) 3K (-5%), 6K (+5%)

ELECTRICAL PARAMETERS	Total Power :	15W
	Ballast Make :	"HYBEC" BIS Approved
	LED Current :	DC 300mA
	Input Voltage :	220-240 V AC
	Rated Frequency :	50/60Hz
	Power Factor :	0.90
	THD Ballast :	<10%
Life Span :	50,000 hrs	


APPLICATION	IP Rated :	IP20
	Use :	Indoor
	Installation :	Recessed Ceiling Mounted.

FITTING SIZE	Dia :	Ø105mm
	Depth :	87mm
	Cut-Out :	Ø90mm

Product Code : F11+HLM-2125
Power : 25W



Powered by:
BRIDGELUX
The Magic of Light™



HOUSING	LED Housing :	Aluminium Die-Casting
	Body Finish :	White Powder Coated
	Reflector :	Metallized PC
	Heat Shrink :	Aluminium Die-Casted Powder Coated

TECHNICAL SPECIFICATION	Light Source :	BRIDGELUX LED
	Beam Angle :	40°
	CCT :	3000K / 4000K / 5000K
	CRI :	80
	Chip Lumens (4K) :	3000 LM (120Lm/w)
	System Lumens (4K) :	2875 LM (115Lm/w) 3K (-5%), 6K (+5%)

ELECTRICAL PARAMETERS	Total Power :	25W
	Ballast Make :	"HYBEC" BIS Approved
	LED Current :	DC 700mA
	Input Voltage :	220-240 V AC
	Rated Frequency :	50/60Hz
	Power Factor :	0.90
	THD Ballast :	<10%
Life Span :	50,000 hrs	

APPLICATION	IP Rated :	IP20
	Use :	Indoor
	Installation :	Recessed Ceiling Mounted.

FITTING SIZE	Dia :	Ø125mm
	Depth :	117mm
	Cut-Out :	Ø115mm